

ViziPrint® Impress

Print Media

To ensure proper usage of ViziPrint® Impress printable window film, please follow the recommendations listed below.

1. Use care when transporting the graphic and removing the release liner. The graphic should not be bent or distorted because ViziPrint® Impress' proprietary suction technology is not substantial enough to hold distortions in the film to the surface.
2. ViziPrint® Impress will adhere to most smooth surfaces such as glass, aluminum, stainless steel, laminated surfaces, and plastics.
3. The surface where the graphic is to be applied must be clean and free of dust and dirt particles. A small amount of debris will not allow the proprietary suction technology to flow out properly and may cause small air pockets in the image.
4. Clean the surface with a suitable cleaner that will not leave streaks or residue on the surface. An adhesive or static roller can be used to remove any debris left behind during initial cleaning.
5. A low tack tape, such as painter's tape, can be used to position the graphic in the correct location and straight on the surface. Put a small piece of tape on the surface to help line up the top and side edges of the graphic.
6. To apply small graphics, carefully pull back the release liner from one edge. Using a piece of tape may be helpful to separate the release liner from the graphic and can prevent damage to the film.
7. Completely remove the remainder of the release liner. Do so carefully as static may be present. Apply one edge of the graphic in the desired position, slowly flexing the image toward the mounting surface so the suction process can occur. This will allow air to escape instead of getting trapped behind the graphic.
8. When installing larger graphics, do not completely remove the release liner before starting the application process. Pull back a few inches of the release liner on the edge of the graphic and use a felt pad to apply it to the surface. As the graphic is applied, pull back the release liner to expose the back and slowly flex the image toward the mounting surface so the suction process can occur.
9. Once the graphic is installed, carefully work out any air bubbles with a felt pad. Graphics can be repositioned due to ViziPrint® Impress' proprietary suction technology. If an image needs to be pulled back and re-installed, it can be done without damaging the graphic's ability to stick to the mounting surface.

IMPORTANT NOTE:

Please refer to the ViziPrint® Impress TDS and MSDS for more information.

The technical information, recommendations and other statements contained in this document are based upon testing and experience Drytac believes to be reliable, but the accuracy and or completeness is not guaranteed. Drytac recommends a small test be performed to determine suitability beforehand. This document does not constitute a warranty of any kind.