

### Interlam™ Pro Anti-Graffiti

*Overlaminating Film*

Interlam™ Pro Anti-Graffiti is a 0.8 mil (20µ) high performance PCTFE film with strong anti-graffiti characteristics and a pressure sensitive acrylic adhesive that is protected by a siliconized PE coated paper release liner. The film is flame resistant and provides a high degree of resistance to ultraviolet light, dirt and pollutants, and the gloss finish offers superb clarity, detail and color contrast. It wipes clean of virtually any spray paint and can be cleaned with most solvents and detergents without adverse effect. The premium adhesive creates a strong bond to UV inks as well as latex and other ink technologies.

#### Typical Applications

- Ideal for retail advertising graphics, event graphics or displays where graffiti might be a possibility, such as outdoor bus shelters, train stations and kiosks.
- Can be used for construction barricade applications.
- Can be used for long-term exterior applications.

#### Product Structure

Film	High Performance PCTFE	2 mil (50µ)
Adhesive	Acrylic (Pressure Sensitive)	
Release Liner	Siliconized PE Coated Paper	

#### Physical Characteristics

Film Thickness	0.8 mil (20µ)
Adhesive Layer	1.2 mil (30µ)
Film/Adhesive Ratio	0.8:1.2
UV Protection Factor	UV resistant
Outdoor Durability	5 years
Service Temperature Range	-13°F to 302°F (-25°C to 150°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

#### Process Settings

Equipment Type	Temperature	Speed
Roller Laminator	Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended	

#### IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.