

MediaTac[™]

Mounting Adhesive

MediaTac[™] is a 0.5 mil (12μ) clear PET film, coated on both sides with a pressure sensitive acrylic adhesive, one of which is protected by a bleached clay coated Kraft paper siliconized on both sides with a differential release. The adhesive is self-wound on the release liner.

Typical Applications

- Developed for photo labs where a high grade of moisture stability within the mounting film is required.
- Ideal for high-volume mounting, including pre-coating boards and image decal applications.
- Recommended for mounting prints to smooth, porous substrates, such as white display board, foam boards, Gatorfoam[™], and tempered hardboard.

Product Structure

Adhesive	Acrylic (Pressure Sensitive)	2.5 mil (62μ)
Film	Clear PET	
Adhesive	Acrylic (Pressure Sensitive)	
Release Liner	2 Side Clay Coated, 2 Side Siliconized Kraft	

Physical Characteristics

Film Thickness	0.5 mil (12μ)
Adhesive Layer	1 mil (25μ) on each side
Film/Adhesive Ratio	1:0.5:1
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Service Temperature Range	-4°F to 248°F (-20°C to 120°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

Process Settings

Equipment Type	Temperature	Speed
Roller Laminator	Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended	

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.