

ReTac® Duo

Mounting Adhesive

ReTac® Duo is a 1 mil (25µ) clear PET film, coated on both sides with adhesive. It has a permanent adhesive on one side to be used on graphic prints and ReTac® ultra removable adhesive on the other, allowing it to be easily removed and re-positioned for repeated use. ReTac® Duo is designed to adhere to walls, doors or any smooth surface without leaving behind residue or damaging the surface when removed. The adhesive is self-wound on a two-sided, PE coated siliconized Kraft release paper.

Typical Applications

- Ideal for transforming photos, posters, graphics, or news clippings into wall graphics or re-positionable decals.

Product Structure

Adhesive	Permanent Acrylic (Pressure Sensitive)	3 mil (75µ)
Film	Clear PET	
Adhesive	ReTac® ultra removable and re-positionable adhesive	
Release Liner	2 Side PE Coated, 2 Side Siliconized Kraft	

Physical Characteristics

Film Thickness	1 mil (25µ)
Adhesive Layer	1 mil (25µ) on each side
Film/Adhesive Ratio	1:1:1
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Service Temperature Range	-22°F to 284°F (-30°C to 140°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

Process Settings

Equipment Type	Temperature	Speed
Roller Laminator	Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended	

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.