

ReTac® Textures

Print Media

ReTac® Textures is a 6 mil (150µ) printable matte white polymeric PVC film with ReTac® ultra removable adhesive. The film is flame resistant and can be easily applied, re-positioned and removed without surface damage or loss of adhesion. ReTac® Textures is available in a variety of embossed finishes (Canvas, Linen, Sand and Woodgrain) that add depth and visual appeal to static, flat images.

Typical Applications

- Ideal for wall graphics, custom wall murals, interior décor, retail displays, trade show graphics and signage, and textured labels.
- ReTac® Textures has been tested to FTMS 191, Method 5903 for flame resistance, making it perfect for application in public areas that require compliance with strict fire regulations, such as airports, hotels and hospitals.

Print Compatibility

- (Eco) Solvent
- Latex
- UV

Product Structure

Film	Matte White PVC	7 mil (175µ)
Adhesive	ReTac® ultra removable and re-positionable adhesive	
Release Liner	143 gsm 2 Side PE Coated, 1 Side Solventless Siliconized Fine Paper	

Physical Characteristics

Film Thickness	6 mil (150µ)
Adhesive Layer	1 mil (25µ)
Film/Adhesive Ratio	6:1
UV Protection Factor	Not Applicable
Outdoor Durability	2 years
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

Installation Recommendations

Please see Wall Graphic Installation & Removal Instructions for further details. The surface must be clean and smooth and free of defects before application.

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein. Only the correct use of the product will allow satisfactory results. For this reason, DRYTAC is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact DRYTAC at one of the phone numbers listed below.