

### RemoTac<sup>™</sup>

### Mounting Adhesive

RemoTac<sup>™</sup> is a 0.5 mil (12 $\mu$ ) clear PET film, coated on one side with a pressure sensitive, removable acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with siliconized PE. The other side of the film is coated with a pressure sensitive, permanent acrylic adhesive. The adhesive is self-wound on the release liner.

#### Typical Applications

- Ideal for interchangeable signs and graphics for countertops, presentation graphics and retail display boards.
- Easily removes from a variety of substrates, including glass, painted metal and aluminium.
- Recommended for difficult, low energy surfaces due to its high tack.
- Suitable for both indoor and short-term outdoor use.

#### Product Structure

Adhesive	Permanent Acrylic (Pressure Sensitive)	2.5 mil (62 $\mu$ )
Film	Clear PET	
Adhesive	Removable Acrylic (Pressure Sensitive)	
Release Liner	2 Side PE Coated, 2 Side Siliconized Kraft	

#### Physical Characteristics

Film Thickness	0.5 mil (12 $\mu$ )
Adhesive Layer	1 mil (25 $\mu$ ) on each side
Film/Adhesive Ratio	1:0.5:1
UV Protection Factor	UV Stable
Outdoor Durability	3 months
Service Temperature Range	-22°F to 284°F (-30°C to 140°C)
Peel Strength (20 min, FTM1)	12 N/25mm (permanent) 7.5 N/25mm (removable)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

#### Process Settings

Equipment Type	Temperature	Speed
Roller Laminator	Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended	

#### IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.