

### SpotOn® Floor 200

Print Media

SpotOn® Floor 200 is an 8 mil (200µ) embossed printable white matte monomeric PVC film, coated on one side with a dot-patterned, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single sided, siliconised clay coated kraft release liner. This high quality ink receptive embossed white vinyl was specifically developed for easy application. SpotOn® Floor 200 has a post-printed anti-slip rating of R10, according to DIN 51130:2010, which allows for vibrant, slip resistant floor graphics without the need for lamination.

#### Typical Applications

- Ideal for short-term indoor floor applications where graphics are applied to floor or ceramic tiles, sealed wood or concrete, waxed vinyl, marble, or terrazzo.
- Graphics for floor advertising as well as other promotional applications.
- Excellent for applications where easy, tool-free installation is necessary.
- Can be removed within 6 months of initial installation.

#### Installation Recommendations

Please see SpotOn® installation instructions for further details. The surface must be clean and smooth and free of defects before application.

#### Print Compatibility

- (Eco) Solvent
- Latex
- UV

#### Product Structure

Film	200µ White Matte Monomeric PVC	8.8 mil (215µ)
Adhesive	Dot Pattern Removable Polyacrylate	
Release Liner	135 gsm Siliconized 1 Side Bleached Clay Coated Kraft	

#### Physical Characteristics

Film Thickness	8 mil (200µ)
Adhesive Layer	0.6 mil (15µ)
Film/Adhesive Ratio	8.0:0.6
UV Protection Factor	Not Applicable
Outdoor Durability	Internal Use Only
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)
Slip Rating (Post-Printed)	R10 (According to DIN 51130:2010)
Shelf Life	1 year
Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity

Rev August 2017

**IMPORTANT NOTE:** Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein. Only the correct use of the product will allow satisfactory results. For this reason, DRYTAC is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact DRYTAC at one of the phone numbers listed below.