

### Trimount™

### Mounting Tissue

Trimount™ is a 2.6 mil (65µ) pH-neutral white mounting tissue, coated on both sides with a heat-activated solvent acrylic adhesive that is tack-free at normal ambient temperature and does not require a release liner.

#### Typical Applications

- For use in all types of dry mounting presses.
- Recommended for bonding resin-coated photographic paper and printed materials to smooth surfaces.

#### Product Structure

Adhesive	Solvent Acrylic (Heat Activated)	3.6 mil (89µ)
Film	Off White Kraft Paper	
Adhesive	Solvent Acrylic (Heat Activated)	

#### Physical Characteristics

Film Thickness	2.6 mil (65µ)
Adhesive Layer	0.5 mil (12µ) on each side
Film/Adhesive Ratio	0.5:2.6:0.5
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

#### Process Settings

Equipment Type	Temperature	Dwell Time
Roller Laminator	Not recommended	
Press	185°F to 210°F (85°C to 99°C)	60 - 90 seconds

#### IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.