

## ViziPrint® Impress

Print Media

To ensure proper installation of ViziPrint® Impress printable window film, please follow the recommendations listed below.

### Recommendations for Installation

1. Use care when transporting the graphic and removing the release liner. The graphic should not be bent or distorted because the film's proprietary adhesion technology is not substantial enough to hold distortions in the film to the surface.
2. ViziPrint® Impress will adhere to most smooth surfaces such as glass, aluminum, stainless steel, laminated surfaces, and plastics.
3. The surface where the graphic is to be applied must be clean and free of dust and dirt particles. A small amount of debris will not allow the proprietary adhesion technology to flow out properly and may cause small air pockets in the image.
4. Prior to application, clean the surface with a soap and water mixture. Use a window squeegee to remove any excess water and wipe the edges dry with a lint-free cloth. Window cleaners or other chemical products are not recommended as they can leave streaks or residue on the surface.
5. A low tack tape, such as painter's tape, can be used to position the graphic in the correct location and straight on the surface. Put a small piece of tape on the surface to help line up the top and side edges of the graphic.

### Wet Installation

1. Prior to wet installation, create an application solution by mixing 3 drops of dishwashing liquid with 1 gallon of warm water.
2. Thoroughly soak the surface where the graphic is to be placed with the application solution.
3. Hold or place the graphic against the solution-soaked surface with the release liner facing you. The solution will hold the graphic in place.

### IMPORTANT NOTE:



Please refer to the ViziPrint® Impress TDS and MSDS for more information.

The technical information, recommendations and other statements contained in this document are based upon testing and experience Drytac believes to be reliable, but the accuracy and completeness is not guaranteed. Drytac recommends a small test be performed to determine suitability beforehand. This document does not constitute a warranty of any kind.