

***Mactac IMAGin B-Free
Gloss Clear Vinyl 3.1mil
54'' x 164' Window Print Media***

Brochure



Provided by

MyBinding.com

When Image Matters.

Call Us at 1-800-944-4573



BUBBLE FREE DIGITAL MEDIA

Product Guide | Window Films



Frosted, Dusted and Clear
B-free® Air-Egress Digital Media
for Window Graphics.



September 2018

MyBinding.com
5500 NE Moore Court
Hillsboro, OR 97124
Toll Free: 1-800-944-4573
Local: 503-640-5920



The markets first **dry application** large scale window graphics.
The only tools you'll need for a perfect application are tape and a squeegee

What are B-free® Window Films?

JT5796MBF Frosted and **JT5798MBF Dusted** are 3.1 mil matte translucent vinyl with special finishes for etched, sandblasted, or frosted effects. **JT5999MBF Clear** is a 3.1 mil gloss clear vinyl. Graphics can be printed in reverse to be read through glass. The clear acrylic permanent adhesive features Mactac's proprietary air-egress structure for fast, easy, no-mess DRY application and a smooth print surface.

Where B-free Frosted, Dusted and Clear media will work for you:

JT5796MBF Frosted, JT5798MBF Dusted and JT5999MBF Clear can be printed by **solvent, eco-solvent, latex** and **UV** wide-format machines. They are designed to be used on flat or simply curved clear and translucent surfaces and for backlit graphics.

- Proprietary omni-directional, air-egress technology – eliminates trapped air in every direction
- Smooth print surface for high quality printing
- Ideal for reverse printed graphics where outdoor signage may be restricted
- Dry application – no messy application fluid required

ICC profiles for JT5796M BF Frosted, JT5798M BF Dusted and JT5999M BF Clear can be downloaded at mactac.com

Product	Gauge	Adhesive	Liner	Outdoor Durability
JT5796MBF	3.1 mil Frosted	Air-egress, Micro-structured, Repositionable Permanent	80# Polycoated	5 years
JT5798MBF	3.1 mil Dusted Translucent Vinyl		80# Polycoated	5 years
JT5999MBF	3.1 mil Gloss Clear Vinyl		80# Polycoated	5 years

Durability

- Use-life estimate based on accelerated age studies on vertical applications under “normal” environmental conditions.
- Severe environmental conditions will reduce use life.
- Recommendations are believed to be accurate but do not constitute a warranty written or implied. Refer to Mactac® Product Performance Guides and Technical Assistance Bulletins prior to use. Visit mactac.com to download.

Temperature Ranges

- Minimum Application: +50°F (+10°C)
- End Use: -40° to 194°F (-40° to 90°C)

Shelf Life

Two years when stored at 60/77°F (15/25°C) and 50% relative humidity in the original package.

*** For unprinted or plotter cut décor applications, Mactac's MACmark® 700 series Décor film is recommended for an ideal finish.**

For more information about B-free or other Mactac products, partnerships or graphic solutions, call a graphics representative at **866-622-8223**, e-mail Mactac.Americas@mactac.com or visit mactac.com/graphics.

MyBinding.com
5500 NE Moore Court
Hillsboro, OR 97124
Toll Free: 1-800-944-4573
Local: 503-640-5920