

ViziPrint® Air Egress UVL

Print Media

ViziPrint® Air Egress UVL is a 3 mil (75µ) clear PET film with a removable, pressure sensitive acrylic adhesive that is protected by an air egress release paper that imparts micro grooves in the adhesive. The micro grooves allow for easy, bubble-free application of graphics onto glass, acrylic and other non-porous surfaces.

Typical Applications

- Ideal for creating high quality graphics for retail store fronts and POP and backlit displays.
- Can be used for simple, quick applications such as posting a menu to a restaurant window.

Print Compatibility

- Latex
- UV

Product Structure

Film	Clear PET	3.6 mil (90µ)
Adhesive	Removable Acrylic (Pressure Sensitive)	
Release Liner	2 Side PE Coated Structured Release Paper with Texture	

Physical Characteristics

Film Thickness	3 mil (75µ)
Adhesive Layer	0.6 mil (15µ)
Film/Adhesive Ratio	3:0.6
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Application Temperature	>41°F (5°C)
Service Temperature Range	158°F to 203°F (70°C to 95°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

Installation Recommendations

Dry installation is recommended for ViziPrint® Air Egress UVL. Please see ViziPrint® Air Egress installation instructions for further details. The surface must be clean and smooth and free of defects before application.

Printing Recommendations

- Handle material with care prior to printing; use gloves to avoid fingerprints.
- The image can be reverse printed on the printable side. If translucent or opaque window graphics are needed, the image can be backed with white ink or a white self-adhesive vinyl.
- Roll graphics with the release liner on the outside of the roll to prevent the release liner from tunneling.

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.