


Tunnel Control Panel
Lowers for Easy Access



Tunnel Controls



Live Roller Rod Conveyor
w/Optional Teflon Mesh Overlay

Model	PP 160620	PP 180828	PP 180844	PP 220848	PP 261052	PP 361060
Power supply	110V 20 AMP	220V 40 AMP	220V 40 AMP	220V/3PH 50 AMP	220V/3PH 50 AMP	220V/3PH 50 AMP
Machine dimensions	35"x22"x53"(H)	40"x26"x61"(H)	61"x26"x61"(H)	72"x30"x64"(H)	76"x34"x64"(H)	84"x45"x66"(H)
Chamber dimensions	20"x16"x6"(H)	28"x18"x8"(H)	44"x18"x8"(H)	48"x22"x8"(H)	52"x26"x10"(H)	60"x36"x10"(H)
Shipping weight	300 lbs	450 lbs	650 lbs	850 lbs	950 lbs	1300 lbs

Optional tunnel height available in: 12", 16" and 20"

STANDARD FEATURES

- Fully re-circulating air chamber
- 4 directional air flow
- State-of-the-art AC variable speed drive
- Automatic tunnel cool down with shut off
- Thermal overload protection on all motors
- Adjustable air velocity control
- Chromed conveyor rollers and shaft (no rust)
- Solid state digital temperature control
- Live roller rod conveyor
- Sealed bearings on drive and idler shafts
- Locking casters w/leveling screws



OPTIONAL FEATURES

- Dead rollers "polyethylene"
- Teflon mesh belt
- High density rollers
- Non-standard voltage
- Custom paint
- Spare parts kits