

Pro Pack LA-560-CS Automatic Sealer Shrink Wrap System

Instruction Manual



Provided by

MyBinding.com
When Image Matters.

Call Us at 1-800-944-4573

AUTOMATIC "L" SEALER SYSTEM



SPECIFICATIONS	LA-460-E	LA-560-CS
Power supply	220V/1Ph/10 AMPS	
Air consumption	1 CFM @ 80 psi	
Center-seal	n/a	included
Closing conveyor feature	Optional	Included
Max. package dimensions	18.75" x 26.5" x 4"(H)	24" x 18.75" x 7.75"(H)
Max. roll width	22"	23.5"
Packaging speed	up to 30 p/m	
Overall dimensions	42" x 89" x 64.5" (h)	83" L x 56"W x 66" H
Shipping weight	990 lbs.	1,500 lbs.

The Pro Pack Automatic "L" Sealer System offers distinct advantages over other automatic systems: high quality construction, high volume, competitive pricing.

Thanks to its **CENTER SEAL SYSTEM** the seal head can be raised or lowered according to the package height

Advantage of the center-seal

If package height is more than 3 inches, the seal device adjusts to save between 2 to 3 inches of film width. This results in a huge saving on film costs.

STANDARD FEATURES:

- ✚ Center seal system
- ✚ Motorized center seal system
- ✚ Teflon-coated sealing blade
- ✚ Continuous cycle sealing
- ✚ Touch Screen control + PLC
- ✚ Possibility of storing up to 10 different operation programs
- ✚ Double adjustment of the sealing blade temperature, both lengthways and broadways
- ✚ Possibility of packing single packs or multipacks
- ✚ Speed of conveyors electronically adjustable from the control panel

PROCESS STATISTICS:

- ✚ Piece counter batch
- ✚ Measurement of the pack length - Real-time output
- ✚ Control of irregular packs - Reduced power consumption